

8730003 HVWGLVHxDGRSDUDPDLWQODVHxDO
DWPvGHFDEOHGHSDUWUHQDGHVFDLGDGHV
GHFDQDOHVSRVHHFRQHLRQHSXZUWRV5-000
ERUQHUVGHVPRQWDEOHV00LW00VLRQWDF
SURIHVLQRDOHV

(08730003 HV SDVLYR QR UHTXLHUH DOLPHQWDFLyQ SHUR
SXHGHWPPELpQ WUDEDMDU FRQ EDOXQHVDFWLYRV GHORWUR ODGR
H[WUHPRGHODFRQH[LyQOR TXH DPSOLD FRQVLGHUDEOHPHQWH
ODGLVWDQFLDGH[WUDQVPLVLYQ
6RSRUWD WRGRV ORV IRUPDWRV R QRUPDV GH YLGRH XQD
UHVROXFLyQGHKDVWD003

Estándar:	AHD, HD-TVI, HD-CVI, CVBS/Analog - Soporta PA , TSC, SECAM
Tipo de dispositivo:	%DOXQWUDQVFHSWRU SDVLYR
Alimentación:	1R UHTXLHUH SDVLYR
Número de canales.:	000&DQDOHV
Rango de la señal:	1080P/3MP/4MP/5MP
Ancho de banda de video:	[a0+]0D[
Impedancia del conector coaxial:	75 Ω
\$WHQXDFLyQ	!000G%
&DQWLGDG GH HQWUDGDV5-00	4 entra as R 45
3URWHFFLyQGH HQWUDGDVDOLGDGH YLGRN9FRP~QGH PRGR000000V000(&00000000	
07%)	!000000K
Temperatura de funcionamiento:	0 °C ... 55 °C
Humedad relativa del ambiente admisible:	< 95 %
0DWHU LDO	0HWDOLFR000&RORU001HJUR
'LPHQVLRQHV	0000(00000(000000PP
Dimensiones Ca a - Pac aging	530 150 90 mm
3HVR	00000U



Vista frontal:



Esquema de conexiones:

